

**BEARING & TOOL CENTRE** 



### Head Office

 <sup>1st</sup> Floor, Vyapar Bhavan, Kadia Kui, Relief Road, Ahmedabad - 380001.
Ph:- 079 - 22160386, 65254835, 22134835 Mobile : 7819819941, 9375706649 Ahmedabad Branch GF-B-14, Jayraj Complex, Nr. Soni ni Chawl, Odhav, Ahmedabad - 382415. Ph:- 079 - 22890202, 65458950, 65404657, 65400202 Mobile : 7878825197, 7819819938, 9375706648

Website : www.bearingtoolcentre.com, www.bearingtoolscentre.com | Email : info@bearingtoolcentre.com

## Our Sister Concern : RELIEF SERVICE CENTRE

Repairs, Removal of Jaw Error, Bore Gauge Extension, Instrument Modifications & Spares

## Quotation

167 Webster Hardness Tester– Insize Make

| Thickness    | 0.6~6mm       | 0.6~ 8mm      | 0.06~6mm      |
|--------------|---------------|---------------|---------------|
| Model (ISHW) | B70           | B75           | B92           |
| Rs.          | 124416        | 124416        | 124416        |
| Catalog      | Page No. $-2$ | Page No. $-2$ | Page No. $-2$ |
| Thickness    | 0.6~6mm       | 0.6~13mm      | 0.6~8mm       |
| Model (ISHW) | L20           | L20A          | L20B          |
| Rs.          | 127292        | 150262        | 150262        |
| Catalog      | Page No. – 2  | Page No. – 2  | Page No. – 2  |

\*\*\* Warranty -12 Months ,Certificate - No

# Terms & Conditions –

- Goods offered Subject to Prior Sale
- Price Validity: "15 Days from Date of Quotation"
- C.S.T 2% extra against form C. Otherwise 5% without form C For Out of Gujarat Sales only.
- VAT 5% extra for Sales within Gujarat. Prices Ex-Godown Ahmedabad.
- Payment against Proforma Invoice, Packing, Forwarding & Freight extra.
- Bank Detail Kotak Mahindra Bank Ltd.
- Branch Shivranjini
- Bank IFSC Code KKBK 0000 810
- Bank Account No. 08102 00000 2689
- Note While making payment online do mention your Company's name.
- TIN NO 24070901229 , CST No. 24570901229
- We are looking forward to your valued orders.

# WEBSTER HARDNESS TESTER



To measure the hardness of soft metal such as aluminum alloy, copper, brass, soft steel, etc.
According to ASTM B647-84 (2000)

SPECIFICATION

| Code  | ISHW-L20                          | ISHW-L20A   | ISHW-L20B                        | ISHW-B70                                     | ISHW-875                     | ISHW-B92                                |  |
|---|-----------------------------------|---|----------------------------------|--|------------------------------|---|--|
| Application   | for aluminum alloy<br>general use | for aluminum alloy<br>thick workpiece   | for aluminum alloy<br>small tube | for hard<br>aluminum alloy<br>and hard brass | for soft brass<br>and copper | for soft steel and<br>cold-rolled steel |  |
| Thickness<br>requirement<br>of flat workpiece         | 0.6~6mm                           | 0.6~13mm  | 0.6~8mm                          | 0.6~6mm                                      | 0.6~8mm                      | 0.6~6mm                                 |  |
| Internal diameter<br>requirement of<br>tube workpiece | >Ø10mm                            | >Ø10mm  | >2/6mm                           | >Ø10mm                                       | >Ø6mm                        | >Ø10mm                                  |  |
| Wall thickness<br>requirement of<br>tube workpiece    | 0.6-6mm                           | 6~13mm<br>(internal diameter<br>Ø10~23.3mm)<br>0.6~6mm<br>(internal diameter<br>>Ø23.3mm) | 0.6~8mm                          | 0.6~6mm                                      | 0.6~8mm                      | 0.6~6mm                                 |  |
| Hardness range  | 0~20HW                            |   |                                  |  |                              |   |  |
| Min. reading  | 1HW                               |   |                                  |  |                              |   |  |
| Accuracy  | ±0.5HW (at 5~17HW)                |   |                                  |  |                              |   |  |
| Dimension   | 205×30×85mm                       |   |                                  |  |                              |   |  |
| Weight  | 500g                              |   |                                  |  |                              |   |  |

#### STANDARD DELIVERY

| Main unit           | 1pc |
|---------------------|-----|
| Spare indenter      | 1pc |
| Hardness test block | 1pc |
| Wrench              | 1pc |