



# BEARING & TOOL CENTRE



## Head Office

1<sup>st</sup> Floor, Vyapar Bhavan, Kadia Kui,  
Relief Road, Ahmedabad - 380001.  
Ph:- 079 - 22160386, 65254835, 22134835  
Mobile : 7819819941, 9375706649

## Ahmedabad Branch

GF-B-14, Jayraj Complex, Nr. Soni ni Chawl,  
Odhav, Ahmedabad - 382415.  
Ph:- 079 - 22890202, 65458950, 65404657, 65400202  
Mobile : 7878825197, 7819819938, 9375706648

Website : [www.bearingtoolcentre.com](http://www.bearingtoolcentre.com), [www.bearingtoolscentre.com](http://www.bearingtoolscentre.com) | Email : [info@bearingtoolcentre.com](mailto:info@bearingtoolcentre.com)

## Our Sister Concern : RELIEF SERVICE CENTRE

Repairs, Removal of Jaw Error, Bore Gauge Extension, Instrument Modifications & Spares

### Quotation

175 | ANGULAR MACHINE VICES – SUPER PRECISION – GROZ @ With Upto 20 % Discount

CODE	JAW WIDTH ( mm )	JAW OPENING ( mm )	JAW DEPTH ( mm )	PRICE	Catalog
AMV/SP/100	100	100	38	18477	Page No – 2
AMV/SP/150	150	150	45	30264	Page No – 2
AMV/SP/200	200	200	58	46194	Page No – 2

### Terms & Conditions –

- Goods offered - Subject to Prior Sale
- Price Validity: "15 Days from Date of Quotation"
- C.S.T 2% extra against form C. Otherwise 5% without form C For Out of Gujarat Sales only.
- VAT 5% extra for Sales within Gujarat. Prices Ex-Godown Ahmedabad.
- Payment against Proforma Invoice, Packing, Forwarding & Freight extra.
- **Bank Detail** – Kotak Mahindra Bank Ltd.
- **Branch** – Shivranjini
- **Bank IFSC Code** - KKBK 0000 810
- **Bank Account No.** 08102 00000 2689
- Note - While making payment online do mention your Company's name.
- TIN NO 24070901229 , CST No. 24570901229
- We are looking forward to your valued orders.

# GROZ MAKE

ANGULAR MACHINE VICES – SUPER PRECISION - GROZ



## 36 / ANGULAR MACHINE VICES - SUPER PRECISION

- Ideal where jobs requires machining at an angle
- Angular slide can be set upto 45° on either sides
- Fitted with 360° swivel base with 1° increments
- Allows combined rotation along horizontal & vertical axes



The Angular Machine Vice being used for 45° face milling