



BEARING & TOOL CENTRE



Head Office

1st Floor, Vyapar Bhavan, Kadia Kui,
Relief Road, Ahmedabad - 380001.
Ph:- 079 - 22160386, 65254835, 22134835
Mobile : 7819819941, 9375706649

Ahmedabad Branch

GF-B-14, Jayraj Complex, Nr. Soni ni Chawl,
Odhav, Ahmedabad - 382415.
Ph:- 079 - 22890202, 65458950, 65404657, 65400202
Mobile : 7878825197, 7819819938, 9375706648

Website : www.bearingtoolcentre.com, www.bearingtoolscentre.com | Email : info@bearingtoolcentre.com

Our Sister Concern : RELIEF SERVICE CENTRE

Repairs, Removal of Jaw Error, Bore Gauge Extension, Instrument Modifications & Spares

Quotation

Coolent Mixer Pump - Groz Make

Product Brief

Introducing the world's most advanced Coolant Mixers that are virtually maintenance free, highly accurate and provide easy & fast adjustment. Coolant / Liquid Mixers are widely used in Industry for mixing liquid coolant concentrate with water for supply to machines. These also find applications in workshops & garages for mixing water with detergents, antifreeze etc. Traditionally, the Coolant Mixers are designed either with a Needle Valve or using a set of mixing jets. Both these designs have several flaws such as cumbersome & time consuming adjustment, too many parts, prone to blockage, high chance of losing the mixing jets which need to be stored separately etc. The Groz Coolant / Liquid Mixers uses a Rotary Disc Valve which is precision CNC machined from Stainless Steel & is highly accurate. The compact construction & minimal parts makes them easy to install & highly reliable.

Some of the features include

Lightweight Aluminium body

Driven by pressure from water supply

Includes full flow Brass Ball valve & also fitted with 2 back flow preventers

Adjustment of mixing ratio is variable & controlled through a simple turn of the knob

Inbuilt Suction Tube & 2" bung that fits directly onto 55 gal (205 litre) Coolant Drums

WETTED COMPONENTS:

Aluminium, Stainless Steel, Brass, Acetal, PVC, Nitrile Rubber

RECOMMENDED USE:

Cutting / Metal Working Fluids, Select Chemicals, Wind Screen Fluids, Antifreeze, Detergents / Soap Solutions

Ordering Information

Cat. Nr.	Ordering Nr.	Application	Mixing Ratio	Capacity
CMX/1	61100	Metal Working Fluids	0 to 11 %	1100 Litre per Hour (290 Gallons per hour)
CMX/2	61101	Soap Solutions	0 to 57 %	1250 Litre per hour (330 Gallons per hour)
CMX/3	61102	Metal Working Fluids	0 to 9 %	1100 Litre per hour (290 Gallons per hour)



Price Rs

CMX/1 Rs. 9940 /-

CMX/3 Rs. 9940 /-

Discount : 22%