



BEARING & TOOL CENTRE



Head Office

1st Floor, Vyapar Bhavan, Kadia Kui,
Relief Road, Ahmedabad - 380001.
Ph:- 079 - 22160386, 65254835, 22134835
Mobile : 7819819941, 9375706649

Ahmedabad Branch

GF-B-14, Jayraj Complex, Nr. Soni ni Chawl,
Odhav, Ahmedabad - 382415.
Ph:- 079 - 22890202, 65458950, 65404657, 65400202
Mobile : 7878825197, 7819819938, 9375706648

Website : www.bearingtoolcentre.com, www.bearingtoolscentre.com | Email : info@bearingtoolcentre.com

Our Sister Concern : RELIEF SERVICE CENTRE

Repairs, Removal of Jaw Error, Bore Gauge Extension, Instrument Modifications & Spares

Quotation

125	Electric Hoist – Wire rope – Single Phase – with Urgent Stop switch and reinforced breaking switch with position limit, Protection Class upto IP 54 , with Thermal protection device.
-----	---

Model	Method of Use	Catalog	Rated Volt Input Power	Lifting weight	Lifting Speed Mtr / min	Lifting Height mtr	Rs.
PA 200 A	Single Hook	Page No. - 4	220/ 230	100 kg	10	12	6000
	Double Hook		510	200 kg	5	6	
PA 500 A	Single Hook	Page No. - 4	220/ 230	250 kg	10	12	9000
	Double Hook		980	500 kg	5	6	
PA 800 A	Single Hook	Page No. - 4	220/230	400 kg	10	12	15000
	Double Hook		1350	800 kg	5	6	
PA 1000 A	Single Hook	Page No. - 4	220/ 230	500 kg	10	12	18000
	Double Hook		1350	1000 kg	5	6	

126	Trolley – for horizontal movement oh Hoist running on the edge of H shaped track
-----	--

Model	Tested Loading Weight	Catalog	Assembling Height	Moving Speed	Motor Power	Motor Speed	Rs.
TD 500 kg	600 kg	Page No. - 4	3 mtr	16.4 mtr / min	60 W	1400 r / min	6000
TD 1000 kg	1200 kg	Page No. - 4	3 mtr	16.4 mtr / min	120 W	1400 r / min	9000

Terms & Conditions –

- Goods offered - Subject to Prior Sale
- Price Validity: "15 Days from Date of Quotation"
- C.S.T 2% extra against form C. Otherwise 5% without form C For Out of Gujarat Sales only.
- VAT 5% extra for Sales within Gujarat. Prices Ex-Godown Ahmedabad.
- Payment against Proforma Invoice, Packing, Forwarding & Freight extra.
- **Bank Detail** – Kotak Mahindra Bank Ltd.
- **Branch** – Shivranjini
- **Bank IFSC Code** - KKBK 0000 810
- **Bank Account No.** 08102 00000 2689
- Note - While making payment online do mention your Company's name.
- TIN NO 24070901229 , CST No. 24570901229
- We are looking forward to your valued orders.



Model	Method of Use	Rated Volt (V)	Input Power(w)	Rated Capacity(kg)	Lifting Speed (m/min)	Lifting Height (m)	Qty./CTN (pcs)	Packing Size (mm)	G.W./N.W. (kg)					
HGS-B-200	单钩 Single-Hook	AC 220/230/ 240 50/60Hz	480	100	10	12	2	490×425 ×155	24/22					
PA200	双钩 Double-Hook			200	5	6								
HGS-B-250	单钩 Single-Hook		540	125	10	12				525×480 ×165	36/34			
PA250	双钩 Double-Hook			250	5	6								
HGS-B-300	单钩 Single-Hook		600	150	10	12						540×505 ×170	38/36	
PA300	双钩 Double-Hook			300	5	6								
HGS-B-400	单钩 Single-Hook		950	200	10	12		620×240 ×350	33/32					
PA400	双钩 Double-Hook			400	5	6								
HGS-B-500	单钩 Single-Hook		1020	250	10	12								1
PA500	双钩 Double-Hook			500	5	6								
HGS-B-600	单钩 Single-Hook		1200	300	10	12								1
PA600	双钩 Double-Hook			600	5	6								
HGS-B-700	单钩 Single-Hook		1250	350	8	12								1
PA700	双钩 Double-Hook			700	4	6								
HGS-B-800	单钩 Single-Hook		1300	400	8	12		1						
PA800	双钩 Double-Hook			800	4	6								
HGS-B-990	单钩 Single-Hook	1600	500	8	12	1								
PA990	双钩 Double-Hook		990	4	6									



规格 Specification	额定载荷 Rated Capacity (T)	实验载荷 Test Loading Weight (T)	标准运行高度 Assembling Height (m)	运行速度 Moving Speed (m/min)	电机参数 Motor Parameter			能通过的最小弯道半径 Min Radius of Crooked Track Which Can Pass (m)	推荐用工字钢 “工” Steel Beam Recommended		净重 N.W. (kg)
					额定电压 Rated Volt (V)	额定功率 Power (W)	转速 Speed (r/min)		工字钢号 Model of Steel Beam (a)	轨宽 Width of Track (mm)	
TD1	1.0	1.2	3	13	AC 100/110/120 220/230/240 50/60Hz	250	1400	1.5	14-20	80-102	17



Ruian Kaixun Mechanical and Electrical Co. Ltd. was founded in 1998 and operates in 27 cities in China. It is a large scale enterprise and is one of the leading Chinese brand names in Electric Hoists. The company has the ISO9001 quality system certificate and most of its products have obtained the latest European Standard attestations like CE, GS, TUV and EMC. Such standards ensure that the products are safe, technically superior and easy to install. These high quality and durable products are now being Imported and distributed through a wide network of dealers in India.



Electric Hoist

These are available to lift loads from 100kg. to 800 kgs. up to a height of 12 meters; a wide range of models to suit your budget and requirement. These machines come with various safety features like stop switch, limit switch, protection class upto Ip54 and thermal prevention device.

Model No.	With Single Hook			With Double Hook			Input Power watt	Rope diameter mm.	Weight of machine kg.
	Lifting weight kg.	Lifting speed mtr./min.	Lifting height mtr.	Lifting weight kg.	Lifting speed mtr./min.	Lifting height mtr.			
PA200A	100	10	12	200	5	6	510	3	11
PA250A	125	10	12	250	5	6	510	3	11
PA300A	150	10	12	300	5	6	600	3	11
PA400A	200	10	12	400	5	6	980	3.8	16.5
PA500A	250	10	12	500	5	6	980	3.8	16.5
PA600A	300	10	12	600	5	6	1200	3.8	16.5
PA700A	350	10	12	700	5	6	1200	4.5	18
PA800A	400	10	12	800	5	6	1350	4.5	18.5



Electric Trolley

These machines are designed to move horizontally on I-beams/girders for loads up to 1000kg. or 1 tonne. They are used in hang-transportation occasions for mounting equipment in workshops and other applications.

Model No.	Trolley Capacity kg.	Speed of Trolley mtr./min.	Input Power watt	Width of Track mm.
TD0.5	500	16.4	60	68-110
TD1.0	1000	16.4	120	68-110

