



# BEARING & TOOL CENTRE



## Head Office

1<sup>st</sup> Floor, Vyapar Bhavan, Kadia Kui,  
Relief Road, Ahmedabad - 380001.  
Ph:- 079 - 22160386, 65254835, 22134835  
Mobile : 7819819941, 9375706649

## Ahmedabad Branch

GF-B-14, Jayraj Complex, Nr. Soni ni Chawl,  
Odhav, Ahmedabad - 382415.  
Ph:- 079 - 22890202, 65458950, 65404657, 65400202  
Mobile : 7878825197, 7819819938, 9375706648

Website : [www.bearingtoolcentre.com](http://www.bearingtoolcentre.com), [www.bearingtoolscentre.com](http://www.bearingtoolscentre.com) | Email : [info@bearingtoolcentre.com](mailto:info@bearingtoolcentre.com)

## Our Sister Concern : RELIEF SERVICE CENTRE

Repairs, Removal of Jaw Error, Bore Gauge Extension, Instrument Modifications & Spares

## Quotation

173 | Gloss Meter , Range 0.1 / 200GU, Resolution : 0.1GU,

Make	MGW	MGW	Metrix+
Model	GM - 60	GM - 2680	GLS 09
Angle	60°	20° / 60° / 85°	60°
Rs.	28500/-	36000/-	11200/-
Discount	5%	5%	10%
Catalog	Page No.- 2	Page No.- 2	Page No.- 3

## Terms & Conditions –

- Goods offered - Subject to Prior Sale
- Price Validity: "15 Days from Date of Quotation"
- C.S.T 2% extra against form C. Otherwise 5% without form C For Out of Gujarat Sales only.
- VAT 5% extra for Sales within Gujarat. Prices Ex-Godown Ahmedabad.
- Payment against Proforma Invoice, Packing, Forwarding & Freight extra.
- **Bank Detail** – Kotak Mahindra Bank Ltd.
- **Branch** – Shivranjini
- **Bank IFSC Code** - KKBK 0000 810
- **Bank Account No.** 08102 00000 2689
- Note - While making payment online do mention your Company's name.
- TIN NO 24070901229 , CST No. 24570901229
- We are looking forward to your valued orders.

## Glossmeter MGW make

# Glossmeter



GM - 60

## SPECIFICATIONS

- Measuring Range : 0.1/ 200GU
- Accuracy :  $\pm 1.0$  gloss unit ( against reference standard )
- Resolution : 0.1 GU

CODE	ANGLE	PRICE
GM - 60	60 <sup>0</sup>	28,500/-
GM - 2680	20 <sup>0</sup> / 60 <sup>0</sup> / 85 <sup>0</sup>	36,000/-

**METRIX MAKE**



### 1. Features:

Designed and manufactured in accordance With international standard ASTM D523, ASTM D1455, ASTM C346, ASTM C584, ASTM D2457, DIN EN ISO 2813, DIN 67530, EN ISO 7668, JIS Z 8741, MFT 30064, TAPPIT 480, GB 9754, GB/T 13891, GB 7706 and GB 8807. Its technical parameters conform to JJG 696-2002.

### 2. Applications:

Widely used in Floor maintenance, Surface cleaning quality control, Stone and tile gloss measurement, Checking printed matter, Quality control of paint and ink, Polished metal surface, measurement (chrome plating), Inspection of paint protection and waxing, Auto-body paint inspection, Surface inspection of plastic mouldings, Evaluation of detergents and washers, Checking masonry and building exteriors.

### 3. Technical Specifications

Measuring geometry: 60°  
Range: 0.1 to 200 gloss units  
Accuracy:  $\pm 1.0$  gloss unit (against reference standard )  
Resolution: 0.1 gloss unit  
Repeatability:  $\pm 0.5$  GU (0 ... 99.9)  
Measuring area: 7x14mm ellipse  
Data memorized: 254 groups  
Data output: RS 232C serial interface  
Working condition:  
Temperature range: 0°C- 40°C  
Humidity: up to 85%  
Power supply: Lithium Battery  
Size: 140x45x75 mm  
Weight: 305 g

### 4. Accessories

Carrying case.....1pc  
Operation manual.....1pc.  
Power adapter.....1pc.  
Holder with calibration standard...1pc.  
Optic cleaning cloth.....1pc.

### 5. Optional accessories

Cable & software for RS232C.USB adaptor. Bluetooth interface.