



BEARING & TOOL CENTRE



Head Office

1st Floor, Vyapar Bhavan, Kadia Kui,
Relief Road, Ahmedabad - 380001.
Ph:- 079 - 22160386, 65254835, 22134835
Mobile : 7819819941, 9375706649

Ahmedabad Branch

GF-B-14, Jayraj Complex, Nr. Soni ni Chawl,
Odhav, Ahmedabad - 382415.
Ph:- 079 - 22890202, 65458950, 65404657, 65400202
Mobile : 7878825197, 7819819938, 9375706648

Website : www.bearingtoolcentre.com, www.bearingtoolscentre.com | Email : info@bearingtoolcentre.com

Our Sister Concern : RELIEF SERVICE CENTRE

Repairs, Removal of Jaw Error, Bore Gauge Extension, Instrument Modifications & Spares

Quotation

Grease Pump – Groz make, Discount – 22%

| Code | Capacity | Details | Price |
|--------|----------|---------------|-------|
| VGP/6A | 6 kgs | Without Wheel | 5196 |
| VGP/6 | 6 kgs | With Wheel | 5568 |
| VGP10A | 10 kgs | Without Wheel | 5840 |
| VGP10 | 10 kgs | With Wheel | 6294 |
| VGP/15 | 15 kgs | With Wheel | 6846 |
| VGP20 | 20 kgs | With Wheel | 8122 |

Terms & Conditions –

- Goods offered - Subject to Prior Sale
- Price Validity: "15 Days from Date of Quotation"
- C.S.T 2% extra against form C. Otherwise 5% without form C For Out of Gujarat Sales only.
- VAT 5% extra for Sales within Gujarat. Prices Ex-Godown Ahmedabad.
- Payment against Proforma Invoice, Packing, Forwarding & Freight extra.
- **Bank Detail** – Kotak Mahindra Bank Ltd.
- **Branch** – Shivranjini
- **Bank IFSC Code** - KKBK 0000 810
- **Bank Account No.** 08102 00000 2689
- Note - While making payment online do mention your Company's name.
- TIN NO 24070901229 , CST No. 24570901229
- We are looking forward to your valued orders.

Product Brief

Volume grease pump designed for quick & effortless greasing in applications requiring large volume of lubrication everyday. For use with agricultural equipment, excavators & other earth moving equipment & in automotive applications.

Variable Handle Setting:

Can be set for high volume or high pressure grease discharge. Pump delivers up to 9 gm of grease on high volume setting. Fully CNC machined to close tolerances the pump develops up to 4,000 PSI (275 BAR) on high pressure setting.

Includes follower plate

STANDARD COMPONENTS

Steel, Aluminium, Brass & Nitrile Rubber

RECOMMENDED USE

AGI 1, 2 & 3 greases



FEATURES

| |
|--|
| DEVELOPS |
| UP TO 4,000 PSI (275 BAR) ON HIGH PRESSURE SETTING |
| DELIVERS |
| UP TO 9 GM / STROKE ON HIGH VOLUME SETTING |

Ordering Information

| CAT NR. | CAPACITY | DETAILS | BOX QTY. |
|----------------------------|-------------------------|----------------|----------|
| VGP/6A | 6 Kgs | Without Wheels | 1 |
| VGP/6 | 6 Kgs | With Wheels | 1 |
| VGP/10A | 10 Kgs | Without Wheels | 1 |
| VGP/10 | 10 Kgs | With Wheels | 1 |
| VGP/15 | 15 Kgs | With Wheels | 1 |
| VGP/20 | 20 Kgs | With Wheels | 1 |
| SPARE PART AND KITS | | | |
| SA/HOS/VGP10A | 2m x 1/4" ID Spare Hose | | 20 |
| SP/PT/X/15A | Spare Follower Plate | | 25 |
| TK/05/VGP | Repair Kit | | 100 |